

Magic Switch



Article

Item no.	Description
185303	Magic Switch Radar push button, multicolor LED signaling, flush mount, 12-24 V-AC/DC, IP65, white

Scope of delivery

- Motion sensor

Features

Features

- Contactless opening of doors and gates
- A hand movement in front of the push button switches an integrated relay
- IMPULSE or ON/OFF function adjustable
- Multicolor LED ring for orientation and acknowledgement of a command (colors adjustable via DIP switch)
- Non-contact and hygienic: the antimicrobial front limits the spread of germs, bacteria and fungi
- No collision damage due to flush installation

Use

- For all Marantec controls and third-party products

Technical data

- Radio frequency: 2.4 GHz
- Connection type: Conventional
- Contact type: 1 CO
- Outputs:
1 potential-free relay contact (CO)
- Sensoren: Radar
- Protection class: IP65
- Color: White
- Temperature (min.)[°C]: -20
- Temperature (max.)[°C]: 55
- Temperature (min./max.)[°C]: -20/55
- Temperature (min.)[°F]: -4
- Temperature (max.)[°F]: 131
- Range [m]: 0.6
- Operating voltage [V]: 12-24 V-AC 12-24 V-DC
- Operating voltage type: Alternating current or direct current
- Power consumption [VA/W/kW]: 1.5 W
- Contact load (max.):
42 V-AC/DC/0.1 A
- Width [mm]: 80
- Height [mm]: 80
- Depth [mm]: 8
- Packing width: 121
- Packing height: 83
- Packing depth/length: 158
- Packing weight: 0.143
- Freight forwarding articles: No
- GTIN: 4062434013700
- Customs tariff number: 85261000
- Country of origin 1000: Volksrepublik China
- Garantie: -

Accessories

Item no.	Description
185304	Surface-mounted housing Surface mount housing for Magic Switch Chroma, white

Technical drawings

