

Power supply 24 V-DC/2.5 A



Article

Item no.	Description
184827	Power supply 24 V-DC/2.5 A 2 outputs, top hat rail installation

Scope of delivery

- Power supply unit

Features

Features

- Wide universal input voltage range
- Adjustable output voltage
- Connections protected against accidental contact
- Can be installed on DIN rail TS-35/7.5 or TS-35/15

Use

- For all Marantec controllers and third-party products

Technical data

- Connection type: Conventional
- Inputs:
1
- Outputs:
2
- Protection class: IP00
- Temperature (min.)[°C]: -30
- Temperature (max.)[°C]: 70
- Temperature (min./max.)[°C]: -30/70
- Temperature (min.)[°F]: -22
- Temperature (max.)[°F]: 158
- Output power [kW]: 0.06
- Input voltage [V]: 85-264 V/1~
- Output voltage [V]: 24 V-DC
- Nominal frequency [Hz]: 50/60
- Output current [A]: 2.5
- Power consumption [VA/W/kW]: 66.7 W
- Width [mm]: 52.5
- Height [mm]: 90
- Depth [mm]: 54.5
- Width (pitch units): 3
- Packing width: 71
- Packing height: 58
- Packing depth/length: 99
- Packing weight: 0.209
- Freight forwarding articles: No
- GTIN: 4062434014578
- Customs tariff number: 85044060
- Country of origin 1000: Deutschland
- Garantie: -